



<http://www.inext2u.com>

Model no.		CV-200
Machine	CPU	ARM7 32Bit
	Speed	47MHz
	ROM	256Kbytes
	RAM	64Kbytes
RS232 Interface	Port number	2 port
	Connector	DB9RA/M
	Signal	RX , TX , RTS , CTS
	ESD Protection	15KV
	Baud rate	300bps to 115.2Kbps
	Distance	15m @ 9600bps
	Communication	Parity: None, Even, Odd, Space, Mark; Data Bits: 5, 6, 7, 8; Stop Bit: 1, 1.5, 2
	Parameters	Flow Control: None, Software, Hardware
Lan Interface	Port number	1 port
	Connector	RJ45
	Isolation	1.5KV Magnetic
	Speed	10/100Mbps
	Protocols	ICMP, ARP, IP, TCP, UDP, DHCP, HTTP
LED	Red	Power
	Green	Tx/Rx data transfer signal
	Green	10/100 Mbps
	Green	Half/Full duplex
Push button		Parameter Reset
Power	Range	9VDC to 24VDC
	Consumption	Under 0.5watt
	Connector	Jack2.0 Negative out & Positive in
	Protection	Reverse voltage protection
Mechanical	Casing	Plastic case
	Dimension (W*H*D)	70mm *25mm* 100mm
Environmental	Operating temperature	0 to 60 C, 5-95% RH
	Storage temperature	0 to 70 C, 5-95% RH
Approvals	Safety	UL
	EMC	CE, FCC
RoHs & WEEE		RoHs
Warranty		One year